

LIFTSTAR

CBD 15/20 YLi

WALKIE LITHIUM BATTERY PALLET TRUCK

步行式锂电托盘搬运车



产品性能特点: 手提式磷酸铁锂电池包, 充电快, 寿命长, 免维护, 更换便捷, 续航无限; 整车简洁灵巧, 转弯半径小, 自重轻, 适用于狭窄通道作业; 货叉最低离地高度77mm, 适合双面托盘; 多功能手柄, 标配直立行走按钮, 龟速按钮, 操作简单舒适; 可翻盖式金属罩壳, 坚固耐用、方便维修; 可选装平衡轮, 提高行车稳定性。

CHARACTERISTICS: Hand-held LFP model lithium battery makes battery changing easier and more convenient, fast charging and efficient. Compact and flexible, small turning radius, light weight, suitable for narrow aisle operations. Min. Fork lowered height: 77mm, fit for double-deck pallet. Multi-function Handle, upright walking button, turtle speed button, which is simple and comfortable for operation. Clamshell type metal housing, strong and durable, make the maintenance easier. Balance wheels can be installed on both sides to improve running stability.



充电快速
FAST AND
CHARGING



稳定·可靠
STABLE AND
RELIABLE



简洁·灵巧
SIMPLE AND
DEXTEROUS



维修便捷
CONVENIENT
MAINTENANCE

CBD15/20 YLi

LIFTSTAR

特性	Feature	CBD15-YLi	CBD20-YLi(24V)	CBD20-YLi(48V)
1.01 型号	Model	步行式 Walkie	步行式 Walkie	步行式 Walkie
1.02 操作类型	Operating type	1500	2000	2000
1.03 额定载重	Load capacity	kg	kg	kg
1.04 载荷中心距	Load center	mm	600	2000
1.05 轴距	Wheel base	mm	1183	
车轮				
Wheels				
2.01 轮子类型	Wheels type		聚氨酯 PU	
2.02 驱动轮, 平衡轮/承载轮数量 (x=驱动轮)	Wheel quantity no. (x=driven) front/rear		1x+2/4	
2.03 驱动轮尺寸	Driving wheel size	mm	Φ210×70	
2.04 承载轮尺寸	Bearing wheel size	mm	Φ74×60	
尺寸				
Dimension				
3.01 货叉最低离地高度	Min.fork lowered height	mm	77±2	
3.02 货叉最大起升高度	Max.fork lifting height	mm	195	
3.03 最大起升行程	Max.lifting height	mm	115	
3.04 货叉外侧间距	Outside width between forks	mm	560/685	
3.05 货叉内侧间距	Inside width between forks	mm	250/375	
3.06 货叉长度	Fork length	mm	1150	
3.07 货叉宽度	Fork width	mm	155	
3.08 货叉厚度	Fork thickness	mm	55	
3.09 整车全长	Overall length	mm	1660	
3.10 车体宽度	Overall width	mm	560/685	
3.11 整车高度 (含手柄)	Overall height(With handle)	mm	1165	
3.12 整车高度 (不含手柄)	Overall height(Without handle)	mm	618	
3.13 最小转弯半径	Min.Turning radius	mm	1405	
3.14 最小直角堆垛通道宽度 (托盘800×1200, 1200沿货叉放置)	Min.Aisle width for pallets 800×1200	mm	1716	
3.15 最小直角堆垛通道宽度 (托盘1000×1200, 1200沿货叉放置)	Min.Aisle width for pallets 1000×1200	mm	1753	
性能				
Performance				
4.01 最大行驶速度, 满载/空载	Travel speed,laden/unladen	km/h	4/4.5	
4.02 最大起升速度, 满载/空载	Lift speed,laden/unladen	mm/s	35/40	
4.03 最大下降速度, 满载/空载	Lowering speed,laden/unladen	mm/s	65/60	
4.04 爬坡度, 满载/空载	Gradeability,laden/unladen	%	6/16	
4.05 制动类型	Service brake type		电磁制动 Electric	
电气配置				
Electrical configuration				
5.01 驱动电机额定功率S2 60分钟	Traction motor rating at S2 60 min	kW	DC0.75	DC0.9
5.02 起升电机额定功率S3 15%	Lift motor rating at S3 15%	kW		BLDC0.9
5.03 蓄电池电压/标称容量	Battery voltage / capacity	V/Ah	24/20 (选配24/30, 24/40)	24/30 (选配24/40)
5.04 充电器规格	Charger specification	V/A	24/8 (选配24/10)	48/15 (选配48/20)
	重量		48/4 (选配48/5)	
6.01 蓄电池重量 (±5%)	Battery weight (±5%)	kg	3.5	4
6.02 自重 (包含蓄电池, 560*1150)	Service weight with battery	kg	143	144
其他				
Others				
7.01 噪音等级	Sound level	dB(A)	≤75	
7.02 转向类型	Steering type		机械转向 Mechanical	
7.03 驱动控制类型	Drive control type		直流控制 DC	无刷控制 BLDC

