LIFTSTAR

型号/Model：

CTD10-090

插脚式叉车/Legged Forklift Truck

配置及性能：

1.他励驱动电机,爬坡能力强;
2.高强度货叉;
3.标配内置充电机;
4.起升自动电限位,延长电机和电池寿命;

安全:

1.驱动无级调速,安全,静音;
2.控制器多重自动保护系统;
3.紧急反向装置/紧急制动开关。

Configuration and performance:

1.Separately excited motor , Strong climbing ability .
2.High strength forks.
3.Built-in charger is standard.
4.Automatic lifting limit , Motor and battery life extension.

Safety:

1.Stepless speed control system , safe and quiet.
2.Controller with Multiple automatic protection.
3.Emergency reversing device / Emergency brake switch.

车型Type	起升高度mm Lift height	门架类型 Mast type	叉腿外侧间距 mm Outside width between legs	叉腿内侧间距 mm Inside width between legs
CTD10-090	1600/1950	单级/SINGLE STAGE	1120/1270/1420	970/1120/1270

型号/Model：

CTD10-090

插腿式叉车/Legged Forklift Truck

特性 Feature		
型号 Model	—	CTD10
配置号 Configuration NO.	—	090
门架类型 Mast type	—	单级 Single Stage
操作类型 Operating type	—	步行式 Walkie
额定载重 Load capacity	kg	1000
载荷中心距 Load center	mm	600
轴距 Wheel base	mm	1134
车轮 Wheels		
轮子类型(前/后) Wheels type	—	PU
驱动轮/平衡轮/承重轮 数量 Wheel quantity Driving wheel/Balance wheel/Bearing wheel	—	1/1/2
驱动轮尺寸 Driving wheel size	mm	Φ252x67
平衡轮尺寸 Balance wheel size	mm	Φ115x55
承重轮尺寸 Bearing wheel size	mm	Φ115x52
尺寸 Dimension		
标准门架起升高度 Standard lift height	mm	1600/1950
门架作业时整车最大高度 Max extend height	mm	2055/2405
门架缩回时整车静态高度 Mast lowered height	mm	2055/2405
货叉最低高度 Lowered fork height	mm	55
标准货叉规格(长/宽/厚) Fork size(length/width/thickness)	mm	1070/100/40
整车全长 Overall length	mm	1640
车体宽度 Overall width	mm	940
货叉外侧间距 Outside width between forks	mm	200-812
货叉内侧间距 Intside width between forks	mm	0-612
最小转弯半径 Min.Turning radius	mm	1344
最小直角堆垛通道宽度（托盘800×1200，1200沿货叉放置） Min.Aisle width for pallets 800×1200	mm	1894
最小直角堆垛通道宽度（托盘1000×1200，1200沿货叉放置） Min.Aisle width for pallets 1000×1200	mm	1936
最小离地间隙 Min.ground clearance	mm	50
性能 Performance		
最大行驶速度，满载/空载 Travel speed,laden/unladen	km/h	3/3.5
最大起升速度，满载/空载 Lift speed,laden/unladen	mm/s	120/180
最大下降速度，满载/空载 Lowering speed,laden/unladen	mm/s	120/120
爬坡度，满载/空载 Gradeability,laden/unladen	%	5/7
电气配置 Electrical configuration		
驱动电机/起升电机 Drive motor/Lift motor	kW	DC0.63/DC2.0
蓄电池电压 Battery voltage	V	24
蓄电池容量 Battery capacity	Ah	85
制动 Brake	—	电磁/再生 Electromagnetic/Regenerative
控制器型号 Controller	—	自制(选配CURTIS)
重量 Weight		
蓄电池重量 Battery weight	kg	48
自重（包含蓄电池）Service weight with battery	kg	514

*本公司保留更改产品设计和规格的权利，恕不另行通知。