

电动托移式叉车

Electric Stacker Truck

MOON
WALK
功能

电子
转向

交流
驱动

弯道
减速

配置及性能:

1. 货叉倾斜双油缸更平稳;
2. 电子助力转向, 轻便、静音;
3. 双路下降电磁阀, 三种下降速度模式;
4. 交流驱动电机, 无碳刷, 免维护;
5. 起升、前移、倾斜自动限位, 延长电机电池寿命;
6. 标配Moon walk功能, 手柄在任意角度车辆可以直线行驶。

安全:

1. 转弯自动减速功能, 更安全;
2. 货叉高货位, 车辆行驶自动降速;
3. 驱动无级调速, 安全, 静音;
4. 控制器多重自动保护系统;
5. 紧急反向装置/紧急制动开关。

Configuration and performance:

1. Fork tilt, double oil cylinder more smoothly.
2. Electronic power steering system, light and low noise.
3. Two-way magnetic valve, three drop speed mode.
4. AC driving motor, without carbon brush and free maintenance.
5. Lifting, reach, tilt automatic limit, delay motor and battery life.
6. Moon Walk function is STD, handle at any angle, the vehicle goes straight.


Safety:

1. Curve automatic deceleration function, more safe.
2. Goods high position, vehicle automatic reduction.
3. Stepless speed control system, safe and quiet.
4. Controller with Multiple automatic protection.
5. Emergency reversing device/Emergency brake switch.

型号 / Model :

CQDH13/14-850

电动前移式叉车 / Electric Reach Truck





型号 / Model :

CQDH13/14-850

电动前移式叉车 / Electric Reach Truck

| 特性 Feature | | |
|---|------|---------------------------------------|
| 型号 Model | — | CQDH13/14 |
| 配置号 Configuration No. | — | 850 |
| 门架类型 Mast type | — | 三级全自由 Full free 3-stage |
| 操作类型 Operating type | — | 步行式 walkie |
| 额定载重 Load capacity | kg | 1300/1400 |
| 载荷中心距 Load center | mm | 500 |
| 轴距 Wheel base | mm | 1478 |
| 车轮 Wheels | | |
| 轮子类型(前/后) Wheels type | — | PU |
| 驱动轮/平衡轮/承重轮 数量 Wheel quantity Driving wheel/Balance wheel/Bearing wheel | — | 1/0/4 |
| 驱动轮尺寸 Driving wheel size | — | Φ248×75 |
| 承重轮尺寸 Bearing wheel size | — | Φ126×75 |
| 尺寸 Dimension | | |
| 门架前移距离 Reach distance | mm | 0-550 |
| 标准门架起升高度 Standard lift height | mm | 3500/3800/4000/4500/5000/5500 |
| 门架作业时整车最大高度 Max extend height | mm | 4710/5010/5210/5710/6210/6720 |
| 门架缩回时整车静态高度 Mast lowered height | mm | 1914/2014/2081/2248/2415/2582 |
| 自由提升高度 Free lifting height | mm | 1141/1241/1408/1575/1742/1909 |
| 货叉最低高度 Lowered fork height | mm | 55 |
| 标准货叉规格(长/宽/厚) Fork size(length/width/thickness) | mm | 1070/100/40 |
| 整车全长 Overall length | mm | 2225 |
| 车体宽度 Overall width | mm | 1430 |
| 货叉外侧间距 Outside width between forks | mm | 200-812 |
| 货叉侧移距离 Distance shift fork side | mm | 150 |
| 货叉倾斜角度(前/后) Tilt of fork (F/B) | Grad | 4/3 |
| 最小转弯半径, 踏板收起/放下 Min. Turning radius | mm | 1566 |
| 最小直角堆垛通道宽度, 踏板收起/放下(托盘800×1200, 1200跨货叉放置) Min. Aisle width for pallets 800×1200 | mm | 2135 |
| 最小直角堆垛通道宽度, 踏板收起/放下(托盘1000×1200, 1200跨货叉放置) Min. Aisle width for pallets 1000×1200 | mm | 2315 |
| 最小离地间隙 Min. ground clearance | mm | 30 |
| 性能 Performance | | |
| 最大行驶速度, 满载/空载 Travel speed, laden/unladen | km/h | 3.5/4 |
| 最大起升速度, 满载/空载 Lift speed, laden/unladen | mm/s | 130/150 |
| 最大下降速度, 满载/空载 Lowering speed, laden/unladen | mm/s | 100/180 |
| 爬坡度, 满载/空载 Gradeability, laden/unladen | % | 3/5 |
| 电气配置 Electrical configuration | | |
| 驱动电机/起升电机/转向电机 Drive motor/Lift motor/Steering motor | kW | AC1.5/DC4.5/DC0.15 |
| 蓄电池电压 Battery voltage | V | 24 |
| 蓄电池容量 Battery capacity | Ah | 345(可选/option:FAAM 345) |
| 制动 Brake | — | 电磁/再生 Electromagnetic/Regenerative |
| 控制器型号 Controller | — | ZAPI |
| 重量 Weight | | |
| 蓄电池重量 Battery weight | kg | 298 |
| 自重(包含蓄电池) Service weight with battery | kg | 2296 |

*本公司保留更改产品设计和规格的权利, 恕不另行通知。



| 车型 Type | 起升高度 mm Lift height | 叉腿外侧间距 mm Outside width between legs | 叉腿内侧间距 Inside width between legs |
|---------------|-------------------------------|---|-------------------------------------|
| CQDH13/14-850 | 3500/3800/4000/4500/5000/5500 | 1190/1270/1420/1470 | 990/1070/1220/1270 |